

KUDU Progressing Cavity Pumps

Series	Model	Displacement Rate at 500rpm at zero head		Displacement Rate at 100rpm at zero head		Pressure rating in meters of H ₂ O column	Pump O.D. (with collars)		Pump Stator Length		
		m ³ /d	bfpd	m ³ /d	bfpd		mm	in	m	ft	
2 3/8"	15 TP 600	16	97	3.1	19	600	71	2.80	0.90	2.94	
	15 TP 1200	16	97	3.1	19	1200	71	2.80	1.80	5.91	
	15 TP 2400	16	97	3.1	19	2400	78	3.07	3.60	11.81	
	30 TP 650	27	170	5.4	34	650	71	2.80	1.31	4.30	
	30 TP 1300	27	170	5.4	34	1300	78	3.07	2.61	8.56	
	30 TP 2000	27	170	5.4	34	2000	78	3.07	3.32	12.84	
	30 TP 2600	27	170	5.4	34	2600	78	3.07	5.22	17.13	
	80 TP 800	85	535	17	107	800	69	2.70	3.65	11.98	
	80 TP 1200	85	535	17	107	1200	69	2.70	5.50	18.04	
	80 TP 1600	85	535	17	107	1600	69	2.70	7.35	24.11	
80 TP 2000	85	535	17	107	2000	69	2.70	9.20	30.18		
2 7/8"	60 TP 650	66	415	13.2	83	650	80	3.15	1.74	5.71	
	60 TP 1300	66	415	13.2	83	1300	80	3.15	3.48	11.42	
	60 TP 1600	66	415	13.2	83	1600	80	3.15	4.35	14.27	
	60 TP 2000	66	415	13.2	83	2000	80	3.15	5.22	17.13	
	60 TP 2600	66	415	13.2	83	2600	80	3.15	6.97	22.87	
	60 TP 3300	66	415	13.2	83	3300	80	3.15	8.70	28.54	
	100 TP 600	108	679	21.6	136	600	86	3.39	2.61	8.56	
	100 TP 1200	108	679	21.6	136	1200	94	3.70	5.22	17.14	
	100 TP 1500	108	679	21.6	136	1500	94	3.70	6.53	21.42	
	100 TP 1800	108	679	21.6	136	1800	94	3.70	7.83	25.69	
	100 TP 2400	108	679	21.6	136	2400	94	3.70	10.46	34.33	
	240 TP 600	244	1535	48.8	307	600	94	3.70	5.22	17.13	
	240 TP 900	244	1535	48.8	307	900	94	3.70	7.83	25.69	
	3 1/2"	120 TP 1300	120	755	24	151	1300	108	4.24	4.06	13.32
120 TP 2000		120	755	24	151	2000	108	4.24	6.10	20.01	
120 TP 2600		120	755	24	151	2600	108	4.24	8.14	26.71	
120 TP 3300		120	755	24	151	3300	108	4.24	10.17	33.37	
160 TP 1200		160	1006	32	201	1200	102	4.00	4.32	14.18	
160 TP 1500		160	1006	32	201	1500	102	4.00	5.76	18.90	
160 TP 2200		160	1006	32	201	2200	102	4.00	8.64	28.35	
200 TP 1200		194	1220	38.8	244	1200	108	4.24	5.50	18.04	
200 TP 1500		194	1220	38.8	244	1500	108	4.24	6.88	22.56	
200 TP 1800		194	1220	38.8	244	1800	108	4.24	8.25	27.07	
200 TP 2400		194	1220	38.8	244	2400	108	4.24	11.00	36.09	
300 TP 800		300	1887	60	377	800	108	4.24	5.50	18.04	
300 TP 1200		300	1887	60	377	1200	108	4.24	8.25	27.07	
300 TP 1600		300	1887	60	377	1600	108	4.24	11.00	36.09	
4"		180 TP 1000	180	1132	36	226	1000	109	4.29	2.91	9.55
		180 TP 2000	180	1132	36	226	2000	120	4.74	5.82	19.11
	180 TP 3000	180	1132	36	226	3000	120	4.74	8.73	28.64	
	225 TP 1600	225	1415	45	283	1600	120	4.74	5.82	19.11	
	225 TP 2400	225	1415	45	283	2400	120	4.74	8.74	28.66	
	300 TP 600	300	1887	60	377	600	109	4.29	2.91	9.55	
	300 TP 1200	300	1887	60	377	1200	120	4.72	5.82	19.09	
	300 TP 1500	300	1887	60	377	1500	120	4.72	7.28	23.87	
	300 TP 1800	300	1887	60	377	1800	120	4.72	8.73	28.64	
	300 TP 2400	300	1887	60	377	2400	120	4.72	11.64	38.19	
	400 TP 900	400	2516	80	503	900	120	4.72	5.82	19.09	
	400 TP 1350	400	2516	80	503	1350	120	4.72	8.73	28.64	
	400 TP 1800	400	2516	80	503	1800	120	4.72	11.64	38.19	
	500 TP 800	491	3084	100	629	800	120	4.72	5.76	18.90	
	500 TP 1200	491	3084	100	629	1200	120	4.72	8.64	28.35	
	500 TP 1600	491	3084	100	629	1600	120	4.72	11.52	37.80	
	600 TP 600	600	3774	120	755	600	120	4.72	5.82	19.09	
	600 TP 900	600	3774	120	755	900	120	4.72	8.73	28.64	
	600 TP 1200	600	3774	120	755	1200	120	4.72	11.64	38.19	
	600 TP 1500	600	3774	120	755	1500	120	4.72	14.55	47.74	
800 TP 400	870	5472	174	1094	400	120	4.72	5.82	19.09		
800 TP 600	870	5472	174	1094	600	120	4.72	8.73	28.64		
800 TP 800	870	5472	174	1094	800	120	4.72	11.64	38.19		
5"	750 TP 800	750	4718	150	944	800	138	5.43	5.66	18.57	
	750 TP 1200	750	4718	150	944	1200	138	5.43	8.49	27.85	
	1000 TP 860	1085	6825	217	1365	860	138	5.43	8.49	27.85	
	1000 TP 1150	1085	6825	217	1365	1150	138	5.43	11.32	37.14	
	1000 TP 1450	1085	6825	217	1365	1450	138	5.43	14.15	46.42	